



**WANSEMI**  
万芯半导体

**WP4618A**

# **Enhancement Mode N+P-Channel Power MOSFET**

SOP8/N+PMOS/40V/ $\pm 20V$ /1.6V/6.5A/23m $\Omega$

-40V/ $\pm 20V$ /-1.6V/-5A/58m $\Omega$

Rev1.2

---


## 40V N+P-Channel MOSFET

### 1.Features

- ◆ High power and current handling capability
- ◆ Lead free product is acquired
- ◆ Fast switching
- ◆ Surface mount package

### 2.Applications

- ◆ Power Switching Application
- ◆ Load Switching
- ◆ BLDC Motor driver




SOP8  
Pin Description

#### ◆ N-Channel

$V_{DS}$	$R_{DS(on)}$ Typ.	$I_D$
40V	23mΩ @ 10V	6.5A
	33mΩ @ 4.5V	

#### ◆ P-Channel

$V_{DS}$	$R_{DS(on)}$ Typ.	$I_D$
-40V	58mΩ @ -10V	-5A
	71mΩ @ -4.5V	



N-Channel      P-Channel

Schematic Diagram

### 3.Package Marking and Ordering Information

Part no.	Marking	Package	PCS/Reel	PCS/CTN.
WP4618A	4618	SOP8	4,000	48,000

### 4.Absolute Max Ratings at Ta=25°C (Note1)

Parameter	Symbol	N-channel	P-channel	Units	
Drain to Source Voltage	$V_{DSS}$	40	-40	V	
Gate to Source Voltage	$V_{GSS}$	±20	±20	V	
Drain Current (DC),	TA=25 °C	$I_D$	-5	A	
	TA=70 °C	$I_D$	-3.5	A	
Drain Current (Pulse), PW≤300μs	$I_{DM}$	26	-20	A	
Avalanche Energy, Single Pulsed	$E_{AS}$	21.6	19.8	mJ	
Total Dissipation	TA=25 °C	$P_D$	2.0	2.0	W
Junction Temperature	$T_J$	150	150	°C	

Parameter	Symbol	N-channel	P-channel	Units
Storage Temperature	$T_{stg}$	-55 to +150	-55 to +150	°C

Note 1: Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

### 5. Thermal Resistance Ratings (Note 2)

Parameter	Symbol	Value	Unit
Maximum Junction-to-Ambient	$R_{\theta JA}$	62.5	°C/W


Note 2: When mounted on 1 inch square copper board  $t \leq 10$ sec The value in any given application depends on the user's specific board design.

### 6. NMOS Electrical Characteristics at $T_a=25^\circ\text{C}$ (Note 3)


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D = 250\mu\text{A}, V_{GS} = 0\text{V}$	40	45	-	V
Zero-Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 40\text{V}, V_{GS} = 0\text{V}$	-	-	1	$\mu\text{A}$
Gate to Source Leakage Current	$I_{GSS}$	$V_{GS} = \pm 20\text{V}, V_{DS} = 0\text{V}$	-	-	$\pm 100$	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_{DS}=250\mu\text{A}$	1.0	1.6	2.5	V
Static Drain to Source On-State Resistance	$R_{DS(on)}$	$I_D = 5\text{A}, V_{GS} = 10\text{V}$	-	23	30	m $\Omega$
		$I_D = 5\text{A}, V_{GS} = 4.5\text{V}$	-	33	50	m $\Omega$
Input Capacitance	$C_{iss}$	$V_{GS}=0\text{V},$ $V_{DS}=20\text{V},$ Frequency=250KHz	-	642	-	pF
Output Capacitance	$C_{oss}$		-	43.2	-	pF
Reverse Transfer Capacitance	$C_{rss}$		-	37	-	pF
Turn-ON Delay Time	$t_{d(on)}$	$V_{DD} = 20\text{V}$ $V_{GS} = 10\text{V}$ $R_{GEN} = 10\Omega$ $I_D = 3\text{A}$	-	21	-	ns
Rise Time	$t_r$		-	31	-	ns
Turn-OFF Delay Time	$t_{d(off)}$		-	39	-	ns
Fall Time	$t_f$		-	14	-	ns
Total Gate Charge	$Q_g$	$V_{DS} = 20\text{V},$	-	8.3	-	nC
	$Q_{gs}$	$V_{GS} = 10\text{V},$	-	1.3	-	nC
	$Q_{gd}$	$I_D = 6\text{A}$	-	2.3	-	nC
Diode Forward Voltage	$V_{FSD}$	$I_S = 6\text{A}, V_{GS} = 0\text{V}$	-	0.88	1.2	V




### NMOS Typical electrical and thermal characteristics




Output Characteristics




Transfer Characteristics




Drain-Source On-Resistance




Drain-Source On-Resistance




Rdson vs Vgs




Gate Charge




Source- Drain Diode Forward



Capacitance vs Vds



Safe Operating Area




Normalized Maximum Transient Thermal Impedance

**7.PMOS Electrical Characteristics at Ta=25°C**


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D = -250\mu A, V_{GS} = 0V$	-40	-47	-	V
Zero-Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = -40V, V_{GS} = 0V$	-	-	-1	$\mu A$
Gate to Source Leakage Current	$I_{GSS}$	$V_{GS} = \pm 20V, V_{DS} = 0V$	-	-	$\pm 100$	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_{DS}=-250\mu A$	-1.0	-1.6	-2.5	V
Static Drain to Source On-State Resistance	$R_{DS(on)}$	$I_D = -5A, V_{GS} = -10V$	-	58	84	m $\Omega$
		$I_D = -5A, V_{GS} = -4.5V$	-	71	117	m $\Omega$
Input Capacitance	$C_{iss}$	$V_{GS}=0V,$ $V_{DS}=-15V,$ Frequency=250KHz	-	933	-	pF
Output Capacitance	$C_{oss}$		-	621	-	pF
Reverse Transfer Capacitance	$C_{rss}$		-	390	-	pF
Turn-ON Delay Time	$t_{d(on)}$	$V_{DD} = -20V$ $I_D = -5A$ $V_{GS} = -10V$ $R_{GEN} = 2.5\Omega,$	-	6.5	-	ns
Rise Time	$t_r$		-	14	-	ns
Turn-OFF Delay Time	$t_{d(off)}$		-	34	-	ns
Fall Time	$t_f$		-	18	-	ns
Total Gate Charge	$Q_g$	$V_{DS} = -20V,$	-	7.1	-	nC
	$Q_{gs}$	$V_{GS} = -10V,$	-	1.5	-	nC
	$Q_{gd}$	$I_D = -5A$	-	1.8	-	nC
Diode Forward Voltage	$V_{FSD}$	$I_S = -6A, V_{GS} = 0V$	-	-0.93	-1.2	V

Note 3: Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


**PMOS Typical electrical and thermal characteristics**




Output Characteristics




Transfer Characteristics




Rdson- Drain Current




Rdson-Junction Temperature




Source- Drain Diode Forward




Capacitance vs Vds



Gate-Charge




Safe Operation Area



Normalized Maximum Transient Thermal Impedance



**8.Package Dimensions**



Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
A	4.70	5.10	C	1.35	1.75
B	3.70	4.10	a	0.35	0.49
L	5.80	6.20	R	0.30	0.60
E	1.27BSC		P	0°	7°
K	0.12	0.22	b	0.40	1.25

## 9. Important Notice

WAN SEMICONDUCTOR (NINGBO) CO.,LTD reserves the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services and to discontinue any product or service. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as “components”) are sold subject to WANSEMI’s terms and conditions of sale supplied at the time of order acknowledgment.

WANSEMI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in WANSEMI’s terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent WANSEMI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

WANSEMI assumes no liability for applications assistance or the design of Buyers’ products. Buyers are responsible for their products and applications using WANSEMI components. To minimize the risks associated with Buyers’ products and applications, Buyers should provide adequate design and operating safeguards.

No WANSEMI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Unless WANSEMI has specifically designated certain components which meet ISO/TS16949 requirements, mainly for automotive use, WANSEMI will not be responsible for any failure of such components to meet such requirements.